UHF Directional Panel Antenna

330-380MHz

BPA3338-65-7





The BPA series panel antennas provide excellent gain with a directional radiation pattern, ideal for coverage requirements in "corridor" and sectorised applications. These panel antennas are fully enclosed to aid installation, provide waterproofing, and to resist bird attack. The main lobe of these antennas is strong, offering excellent beam control, upper side lobe suppression and front to back ratio, ensuring the integrity of the pattern.


Proven design and construction techniques provide not only excellent radiation characteristics but also high levels of intermodulation and noise suppression. IM performance is -145dBc based on a two-carrier test. The antenna rests at ground potential, offers excellent lightning protection and reduced precipitation noise.

Features:

- Analogue and digital technology compatible
- Ideal for highly populated sites requiring "corridor" or sectorised coverage
- Industry leading PIM ratings (-145dBc) providing low IM and low noise characteristics for optimum performance
- Convenient mounting style suits various pole, mast and wall installation locations
- Mechanical tilt mounting brackets supplied
- DC grounded for superior lightning protection









Specifications

Model Number	BPA3338-65-7
Nominal Gain dBi (dBd)	7 (5)
Frequency MHz	330-380
Tuned Bandwidth MHz	Entire band
Polarity	Vertical
VSWR (Return Loss)	<1.8:1 (10dB)
Nominal Impedance Ω	50
Downtilt	0° to 10° adjustable
Vertical Beamwidth °	65 typ.
Horizontal Beamwidth °	65 typ.
Front to Back Ratio dB	> 16
Input Power W	500
Passive IM 3rd order dBc	-145

Mechanical

Model Number	BPA3338-65-7
Construction	Fully enclosed in radome
Length x Width x Depth mm (in)	700 x 560 x 180 (27.6 x 22 x 7.1)
Weight kg (lbs)	14 (31)
Weight including clamps kg (lbs)	18 (40)
Termination	1 x DIN female
Clamps (provided)	Adjustable downtilt style
Clamp Diameter mm (in)	Suits Ø70 to Ø120 (Ø2.76 to Ø4.72)