



PRODUCT LINE - Mobile & Terminal Antennas / LTE Mobile Antennas

Part Number	Product Name	Conn. Type	Freq MHz	Power W	Band	Color	Impedance	Nominal Gain dBi	Radiator Material	Termination	Tunable Bandwidth
TLA2100	3G/4G Cellular Transit Antenna, 824-2170MHz, 5M Terminated SMA (M)	-	824-960MHz /1710-2170MHz	10	824-2170MHz	White	50	2	White Gelay ASA	5M of 9006 cable/SMA connector	Full
CD7195-W	4G LTE Cellular Mobile Antenna, Fixed Whip, 6.5dBi Gain, White, 698-2700MHz	-	698-960MHz, 1710-2170MHz & 2300-2700MHz	10	698-2700MHz	White	50	6.5 / 4.5 / 5.5	Flexible PCB	5m 9006 (RG58) low loss cable terminated with FME female connector	Full
CD7197-B	4G LTE Cellular Mobile Antenna	-	698-960MHz, 1710-2170MHz & 2300-	10	698-2700MHz	Black	50	7.5/4.5/5.5	Flexible PCB	5m 9006 (RG58) low loss cable t	Full

Part Number	Product Name	Conn. Type	Freq MHz	Power W	Band	Color	Impedance	Nominal Gain dBi	Radiator Material	Termination	Tunable Bandwidth
	na. Fixed Whip. 7.5dBi Gain. Black. 698-2700M Hz		2700M Hz							terminated with FME female connector	
CD7197-W	4G LTE Cellular Mobile Antenna. Fixed Whip. 7.5dBi Gain. White. 698-2700M Hz	-	698-960MHz , 1710-2170 MHz & 2300-2700M Hz	10	698-2700M Hz	White	50	7.5/4.5/5.5	Flexible PCB	5m 9006 (RG58) low loss cable terminated with FME female connector	Full
CD7194-B	4G LTE Cellular Mobile Antenna. Fixed Whip. 5.5dBi Gain. Black. 698-2700M Hz	-	698-960MHz , 1710-2170 MHz & 2300-2700M Hz	10	698-2700M Hz	Black	50	5.5/4.5/5.5	Flexible PCB	5m 9006 (RG58) low loss cable terminated with FME female connector	Full
CD7195-B	4G LTE Cellular Mobile Antenna. Fixed Whip. 6.5dBi Gain. Black. 698-2	-	698-960MHz , 1710-2170 MHz & 2300-2700M Hz	10	698-2700M Hz	Black	50	6.5 / 4.5 / 5.5	Flexible PCB	5m 9006 (RG58) low loss cable terminated with FME female connector	Full

Part Number	Product Name	Conn. Type	Freq MHz	Power W	Band	Color	Impedance	Nominal Gain dBi	Radiator Material	Termination	Tunable Bandwidth
	700M Hz										
CDQ7195-B	4G LTE Q-Fit Mobile Cellular Mobile . Removable Whip. 6.5dBi Gain. Black	-	698-960MHz , 1710-2170 MHz & 2300-2700M Hz	10	698-2700M Hz	Black	50	6.5 / 4.5 / 5.5	Flexible PCB	5m 9006 (RG58) low loss cable terminated with FME female connector	Full
CDQ7199-B	4G LTE Q-Fit Mobile Cellular Mobile . Removable Whip. 8.5dBi Gain. Black	-	698-960MHz , 1710-2170 MHz & 2300-2700M Hz	10	698-2700M Hz	Black	50	8.5/4.5/5.5	Flexible PCB	5m 9006 (RG58) low loss cable terminated with FME female connector	Full
CDQ7195-W	4G LTE Q-Fit@ Mobile Cellular Mobile . Removable Whip. 6.5dBi Gain. White	-	698-960MHz , 1710-2170 MHz & 2300-2700M Hz	10	698-2700M Hz	White	50	6.5 / 4.5 / 5.5	Flexible PCB	5m 9006 (RG58) low loss cable terminated with FME female connector	Full
CDQ7199-W	4G LTE Q-Fit@ Mobile Cellular Mobile . Removable Whip. 8.5dBi	-	698-960MHz , 1710-2170 MHz & 2300-2700M Hz	10	698-2700M Hz	White	50	8.5/4.5/5.5	Flexible PCB	5m 9006 (RG58) low loss cable terminated with FME female	Full

Part Number	Product Name	Conn. Type	Freq MHz	Power W	Band	Color	Impedance	Nominal Gain dBi	Radiator Material	Termination	Tunable Bandwidth
	Gain, White									connector	
LTE-M AGS-3M-SMA	Cellular LTE Magnetic Mount Antenna, 698-2700MHz	-	698-960MHz, 1710-2170MHz, & 2500-2700MHz	25	698-2700MHz	Black	50	1.8/3.1/2.9	PC/AB C UV Stable	3M RG174/SMA Male	Full
CSM600-MAG-4M-SMA	LTE Cellular Magnetic Antenna, 698-2700MHz	-	698-960 / 1710-2170 / 2300-2700 MHz	10	698-2700MHz	Black	-	2.5/3.3/4.6	UV Stable ABS	4M RG58C/U / SMA Male	Full
CD1625-SRG	LTE Cellular Mobile Elevated Feed Antenna 3dB Gain, 809MHz-1880MHz	-	890-960MHz / 1710-1880MHz	50	890-1880MHz	Black	-	3dB over a 1/4 wave	17-7PH Stainless steel black finish	SMA RG Fitted	Full
CSM700-0.5-VA1	LTE Compact Stud Antenna, 698-2700MHz, 0.5M Terminated RA SMA (M)	-	698-960 / 1710-2170 / 2300-2700 MHz	10	698-2700MHz	Black	50	2.0/3.5/5.0	UB Stable Black Polycarbonate	0.5M RG58/SMA Male	Full
CSM700-1.25M-SMA	LTE Compact Stud Antenna, 698-2700MHz	-	698-960 / 1710-2170 / 2300-2700 MHz	10	698-2700MHz	Black	50	2.0/3.5/5.0	UB Stable Black Polycarbonate	1.25M RG58/SMA Male	Full

Part Number	Product Name	Conn. Type	Freq MHz	Power W	Band	Color	Impedance	Nominal Gain dBi	Radiator Material	Termination	Tunable Bandwidth
	MHZ, 1.25M Terminated RA SMA (M)		MHz								
CSM700-N	LTE Compact Stud Antenna, 698-2700 MHz, Integrated N-Connector (F)	-	698-960 / 1710-2170 / 2300-2700 MHz	10	698-2700MHz	Black	50	2.0/3.5/5.0	UB Stable Black Polycarbonate	Integrated N-connector (F)	Full
TLA4100	LTE Transit Antenna, 698MHz-2700 MHz & 5.8GHz	-	698-960MHz / 1710-2170MHz / 2300-2700MHz / 5700-5800MHz	100	698-960MHz / 1710-2170MHz / 2400-2700MHz & 5700-5800MHz	White	50	5/6/3/7	NF-F-16-102 compliant injection moulded radome	Antenna Port: Fixed N-female GPS: TNC Female	Full. No tuning required
LTE-GSDA-1.5M-SMA	LTE/GPS Dome Antenna, 698-2700MHz & GPS/GLONASS	-	698-960MHz, 1710-2170MHz, & 2500-2700MHz	25	698-2700MHz	Black	50	2/4/3.5	ASA	2 x 1.5m RG174 / SMA Male	Full
TLA4200	LTE/GPS Transit Antenna, 698 MHz-2700 MHz & 5.8 GHz GPS	-	698-960MHz / 1710-2170MHz / 2300-2700MHz / 5700-5800MHz / GPS (1575.42M	100	698-960MHz / 1710-2170MHz / 2400-2700MHz / 5700-5800MHz and	White	-	5/6/3/7/28	NF-F-16-102 compliant injection moulded radome	Antenna Port: Fixed N-female GPS: TNC Female	Full. No tuning required

Part Number	Product Name	Conn. Type	Freq MHz	Power W	Band	Color	Impedance	Nominal Gain dBi	Radiator Material	Termination	Tunable Bandwidth
			Hz)		GPS (1575.42MHz)						
LMHP-1.5M-FS	LTE/WIFI MIMO & GPS Low Profile Antenna. 698-2700MHz/2.4 & 5GHz	-	LTE - 698-960 & 1710-2170MHz/ WIFI - 2.4 & 5GHz/ GPS - 1575.42MHz	50	698-2700MHz/2.4 & 5GHz/1575.42MHz	Black	-	LTE - 2/4; WIFI - 2.4-2.5/5.7/5.8; GPS - 28	UV Stable ABS	2 x 1.5m RG174 / SMA Male	Full. No tuning required
LMHP-G-1.5M-FS	LTE/WIFI MIMO & GPS Low Profile Antenna. 698-2700MHz/2.4 & 5GHz	-	LTE - 698-960 & 1710-2170MHz/ WIFI - 2.4 & 5GHz/ GPS - 1575.42MHz	50	698-2700MHz/2.4 & 5GHz/1575.42MHz	Black	-	LTE - 2/4; WIFI - 2.4-2.5/5.7/5.8; GPS - 28	UV Stable ABS	3 x 1.5m RG174 / SMA Male	Full. No tuning required
LMHP-GW-1.5M-FS	LTE/WIFI MIMO & GPS Low Profile Antenna. 698-2700MHz/2.4 & 5GHz	-	LTE - 698-960 & 1710-2170MHz/ WIFI - 2.4 & 5GHz/ GPS - 1575.42MHz	50	698-2700MHz/2.4 & 5GHz/1575.42MHz	Black	-	LTE - 2/4; WIFI - 2.4-2.5/5.7/5.8; GPS - 28	UV Stable ABS	5 x 1.5m RG174 / SMA Male	Full. No tuning required
LTE-M DA-1.5M-SMA	MIMO LTE Cellular Dome Antenna. 698-2700MHz	-	698-960MHz, 1710-2170MHz, & 2500-2700MHz	25	698-2700MHz	Black	50	(-0.8)/2.5/3.4	ASA	2 x 1.5m RG174 / SMA Male	Full

Part Number	Product Name	Conn. Type	Freq MHz	Power W	Band	Color	Impedance	Nominal Gain dBi	Radiator Material	Termination	Tunable Bandwidth
TLA3100	Multi-Band TLA Style Cellular Transit Antenna, 824-2170MHz or GPS	-	824-960MHz /1710-2170MHz	10	824-2170MHz, GPS (1575.42MHz)	White	50	2	White Gelay ASA	5M of 9006 cable/SMA M connector, 5m of RG174 cable with an MCX connector	Full
LTE-SDA-1.5M-SMA	SISO LTE Cellular Dome Antenna, 698-2700MHz	-	698-960MHz, 1710-2170MHz, & 2500-2700MHz	25	698-2700MHz	Black	50	0.7/3.4/4.0	ASA	1.5m RG174 / SMA Male	Full