


PRODUCT LINE - Control Station Combiners / Broadband Short Haul

Part Number	Product Name	Freq Band	Freq MHz	Channel Capacity	Insertion Loss dB @ UHF	Operating Temp. Range	T/R Port-Port Isolation dB
CS0496-16 05-31	Broadband Short-Haul Control station combiner, 40-960 MHz, 16 Channel	Broadband	40 to 960 MHz	16	35dB +/- 2.5dB	-30 to +50°C / -22 to +122°F	60dB typ.
CS0496-24 05-31	Broadband Short-Haul Control station combiner, 40-960 MHz, 24 Channel	Broadband	40 to 960 MHz	24	38.5dB +/-2.5dB	-30 to +50°C / -22 to +122°F	60dB typ.
CS0496-32 05-31	Broadband Short-Haul Control station combiner, 40-960 MHz, 32 Channel	Broadband	40 to 960 MHz	32	38.5dB +/-2.5dB	-30 to +50°C / -22 to +122°F	60dB typ.
CS0496-04 05-31	Broadband Short-Haul Control Station Combiner, 40-960 MHz, 4 Channel	Broadband	40 to 960 MHz	4	27.5dB +/-1dB	-30 to +50°C / -22 to +122°F	60dB typ.

Part Number	Product Name	Freq Band	Freq MHz	Channel Capacity	Insertion Loss dB @ UHF	Operating Temp. Range	T/R Port-Port Isolation dB
CS0496-08 05-31	Broadband Short-Haul Control Station Combiner, 40-960 MHz, 8 Channel	Broadband	40 to 960 MHz	8	30.5dB +/-1dB	-30 to +50°C / -22 to +122°F	60dB typ.