


PRODUCT LINE - Site Monitoring / Antenna System Monitoring

Part Number	Product Name	Conn. Type	Freq Band	Freq MHz	DC Power Connector	Frequency Range	Power Supply
ASM7487-48	700/800 MHz Antenna System Monitor, 7 40-870MH z. 36-60V DC	-	700/800	746 to 870MHz	Polarised 2-pin Phoenix connector	(Tx power and Rx level monitoring) 746-870 MHz	11-36VDC, 36-60VDC or 100-240 VAC (note # 2)
ASM7487	700/800 MHz Antenna System Monitor, 7 40-870MH z. 9-36V DC	-	700/800	746 to 870MHz	Polarised 2-pin Phoenix connector	(Tx power and Rx level monitoring) 746-870 MHz	11-36VDC, 36-60VDC or 100-240 VAC (note # 2)
ASM7487-AC	700/800 MHz Antenna System Monitor, 7 40-870MH z. 90-246VAC	-	700/800	746 to 870MHz	Polarised 2-pin Phoenix connector	(Tx power and Rx level monitoring) 746-870 MHz	11-36VDC, 36-60VDC or 100-240 VAC (note # 2)
ASM8796-48	900 MHz Antenna System Monitor, 8 70-960MH z. 36-60V DC	-	800/900	870 to 960MHz	Polarised 2-pin Phoenix connector	(Tx power and Rx level monitoring) 870-960 MHz	11-36VDC, 36-60VDC or 100-240 VAC (note # 2)
ASM8796	900 MHz Antenna System	-	800/900	870 to 960MHz	Polarised 2-pin Phoenix	(Tx power and Rx level	11-36VDC, 36-60VDC or 100-240

Part Number	Product Name	Conn. Type	Freq Band	Freq MHz	DC Power Connector	Frequency Range	Power Supply
	Monitor, 8 70-960MHZ z. 9-36V DC					(Tx power and Rx level monitoring) 870-960 MHz	VAC (note # 2)
ASM8796-AC	900 MHz Antenna System Monitor, 8 70-960MHZ z. 90-246VAC	-	800/900	870 to 960MHz	Polarised 2-pin Phoenix connector	(Tx power and Rx level monitoring) 870-960 MHz	11-36VDC, 36-60VDC or 100-240 VAC (note # 2)
ASM3852	UHF Antenna System Monitor, 3 80-520MHZ z	-	UHF	380 to 520MHz	Polarised 2-pin Phoenix connector	(Tx power and Rx level monitoring) 380-520 MHz	11-36VDC, 36-60VDC or 100-240 VAC (note # 2)
ASM3852-48	UHF Antenna System Monitor, 3 80-520MHZ z. 36-60VDC	-	UHF	380 to 520MHz	Polarised 2-pin Phoenix connector	(Tx power and Rx level monitoring) 380-520 MHz	11-36VDC, 36-60VDC or 100-240 VAC (note # 2)
ASM3852-AC	UHF Antenna System Monitor, 3 80-520MHZ z. 90-246VAC	-	UHF	380 to 520MHz	Polarised 2-pin Phoenix connector	(Tx power and Rx level monitoring) 380-520 MHz	11-36VDC, 36-60VDC or 100-240 VAC (note # 2)
ASM1317	VHF Antenna System Monitor, 1 32-174MHZ z.	-	VHF	132 to 174MHz	Polarised 2-pin Phoenix connector	(Tx power and Rx level monitoring) 132-174 MHz	11-36VDC, 36-60VDC or 100-240 VAC (note # 2)
ASM1317-48	VHF Antenna System Monitor, 1 32-174MHZ z. 36-60VDC	-	VHF	132 to 174MHz	Polarised 2-pin Phoenix connector	(Tx power and Rx level monitoring) 132-174 MHz	11-36VDC, 36-60VDC or 100-240 VAC (note # 2)
ASM1317-AC	VHF Antenna System Monitor, 1 32-174MHZ z.	-	VHF	132 to 174MHz	Polarised 2-pin Phoenix connector	(Tx power and Rx level monitoring) 132-174 MHz	11-36VDC, 36-60VDC or 100-240 VAC (note # 2)



RFI Americas

Part Number	Product Name	Conn. Type	Freq Band	Freq MHz	DC Power Connector	Frequency Range	Power Supply
	90-246VA						
	C						

2023, Case Parkway North
 Twinsburg, OH 44087
 Phone: (330)-486-0706, Fax: (330)-486-0705
 sean.johnson@rfi.com.au, steve.lehman@rfi.com.au